



# Commercial Substrate Evaluation Report

Certified for **HP Indigo** 

Supplier Information									
Supplier Name	Sappi Europe								
Supplier Address	16	66 Chaussée de la H	ulpe, Bru	ıssels, B-1170					
Supplier Country	Belgium								
Product Information									
Product Name	Eu	EuroArt plus gloss							
Product Category	Pa	Paper							
Grammage (gsm) / Basis weight (#)		300 gsm		Thickness (microns/caliper)		282 um			
Certification Number		RI5500-16-4550		Certification Center		RIT			
Date of Evaluation	06	06/06/2016 Evaluated on		Evaluated on		Interpolation			
Certified for	55	5500, 3050/3500, 5000, 5600 multi-shot, 7000, 7500, 7600, 7800 & 10000							
Evaluation Process	Interpolation								
Evaluation	N	Measurement		Result	Gr	rade (stars)	Comments		
Runability									
Simplex	N	lumber of Jams			***				
Duplex	Ν	lumber of Jams							
Ink Adhesion / Fixing					***				
Peeling	100%K in 4 color mode, % in remaining								
Flaking	<1mm, % Coverage								
Photo Peeling	290K in 4 color mode, % in remaining								
Photo Flaking	<1mm, % Coverage								
Photo Recommended	>80%	>80% after 10 or 60 min							
White Ink Recommended	>80% after 10 or 60 min								
Blanket Compatibility					A A				
Cleaner Pages		ean page after 12K impressions			**				
Evaluation Result	Pass								

Comment Detail:

# The substrate certification procedure incorporates several processes.

An initial screening evaluation is followed by a more comprehensive evaluation looking at the performance of the particular substrate within the press. This checks for:

# **Runnability:**

The ability of the substrate to run smoothly through the press in various print modes.

#### Fixing:

Ink-substrate interaction as determined by: 1) The degree of ink adhesion to the substrate for standard and photo-related applications as measured in a tape peel test of the image; and 2) The degree of flaking of the ink layer. The fixing properties are measured through a range of blanket temperatures and pressures.


## **Blanket Compatibility:**

Blanket-substrate interaction as determined by: 1) Ink-transferability, which is the quality of ink transfer from the blanket to the substrate as reflected in highlight dots, thin lines, heavy images and image edge integrity; 2) 'Blanket Memory' effects, reflected in gloss or density differences between solids and background areas of the previously printed image; and 3) Number of cleaner pages, in which blankets are routinely maintained by performing a self cleaning procedure ("cleaner pages") used to refresh the blanket's release layer.

## **Photo and White Ink Applications:**

Use of robust media products is strongly recommended when printing photo-related and/or white ink applications and/or Light Cyan and Light Magenta due to additional ink coverage demands of these applications. This media has been tested and approved to perform well with higher levels of ink coverage, and is therefore recommended for photo-related and/or white ink type applications. However, it is strongly recommended that user acceptance ultimately be evaluated per individual application and finishing requirements, etc. The test results are provided as a guide; assess actual performance to determine suitability for individual use.

### **Star Rating**



		<b>☆☆☆ ☆☆</b>		*	
Evaluation	Measurement	Best-performing	Recommended	Good	Failure
Transport	Runnability	No jams with the tested paper	No more than 1 jam or minor issue with the tested paper	No more than 1 jam and minor issues with the tested paper	2 jams with the tested paper, control performs well
Fixing	Peeling	Peeling All 4 results are $\geq 90\%$ All 4 results are $\geq 80\%$		At least 1 result is ≥ 80%	All results < 80%
Flaking Guillotine, 5min ● Coated		All results are > 250%	At least 1 result is > 250%	At least 1 result is > 200%	Results < 200%
Flaking Guillotine, 5min ● Uncoated		Result is > 300%	Result is > 250%	Result is > 200%	Results < 200%
Photo	Peeling 290% Black	Result is > 80% after 10 or 60 minutes		N/A	Results < 80%
	Flaking Guillotine, 5min	<1mm	at 350% K	N/A	Results > 1 mm
Blanket Compatibility	Cleaner Sheets 1st Red is clean		3™ Red is clean	5 <sup>th</sup> Red is clean	5th Red not clean, or White observed
	Monitors on tested paper and reference glossy paper up to 12K impressions		Slight memories may be seen up to 12K impressions	Some memories may be seen by 12K impressions	Severe lack of dots/cracks/gloss memory

This substrate is certified for the next two years from the date of evaluation, provided there is no change to the paper properties or production processes. At the end of two years from the original evaluation date, if there have been no changes in paper properties or production processes, the certification can be extended for another two years. After four years from the original certification date, a new certification is required.



