



# Commercial Substrate Evaluation Report

Certified for **HP Indigo** 

| Supplier Information              |      |  |      |                             |              |              |              |  |  |  |
|-----------------------------------|------|--|------|-----------------------------|--------------|--------------|--------------|--|--|--|
| Supplier Name                     |      | Sappi Europe   |      |                             |              |              |              |  |  |  |
| Supplier Address                  |      | 166 Chaussée de la Hulpe, Brussels, B-1170                             |      |                             |              |              |              |  |  |  |
| Supplier Country                  |      | Belgium  |      |                             |              |              |              |  |  |  |
| Product Information               |      |  |      |                             |              |              |              |  |  |  |
| Product Name                      |      | Magno™ Plus Gloss  |      |                             |              |              |              |  |  |  |
| Product Category                  |      | Paper  |      |                             |              |              |              |  |  |  |
| Grammage (gsm) / Basis weight (#) |      | 115 gsm  |      | Thickness (microns/caliper) |              | 90 um        |              |  |  |  |
| Certification Number              |      | RI5500-16-4739   |      | Certification Center        |              | RIT          |              |  |  |  |
| Date of Evaluation                |      | 06/06/2016   |      | Evaluated on                |              | HP 5500      |              |  |  |  |
| Certified for                     |      | 3050/3500, 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 & 10000 |      |                             |              |              |              |  |  |  |
| Evaluation Process                | Full |  |      |                             |              |              |              |  |  |  |
| Evaluation                        |      | Measurement  |      | Result                      | G            | rade (stars) | Comments     |  |  |  |
| Runability                        |      |  | _    |                             |              |              |              |  |  |  |
| Simplex                           |      | Number of Jams   | 0    |                             | $\star\star$ | *            |              |  |  |  |
| Duplex                            |      | Number of Jams   | 0    |                             |              |              |              |  |  |  |
| Ink Adhesion / Fixing             |      |  |      |                             | $\star\star$ | *            |              |  |  |  |
| Peeling                           | 1    | 100%K in 4 color mode,<br>% in remaining 98%                           |      |                             |              |              |              |  |  |  |
| Flaking                           |      | <1mm, % Coverage   |      | 350%                        |              |              |              |  |  |  |
| Photo Peeling                     | 2    | 290K in 4 color mode,<br>% in remaining                                |      | 98%                         |              |              |              |  |  |  |
| Photo Flaking                     |      | <1mm, % Coverage 370%  |      |                             |              |              |              |  |  |  |
| Photo Recommended                 | >    | >80% after 10 or 60 min  |      |                             |              |              |              |  |  |  |
| White Ink Recommended             | >    | 80% after 10 or 60 min   | N/A  |                             |              |              |              |  |  |  |
| Blanket Compatibility             |      |  |      |                             |              |              | Gloss Memory |  |  |  |
| Cleaner Pages                     | 1    | st clean page after 12K<br>impressions                                 |      |                             | **           |              |              |  |  |  |
| Evaluation Result                 |      |  | Pass |                             |              |              |              |  |  |  |

Comment Detail: Gloss Memory - Substrate received a 2 star rating for slight gloss memory after the blanket compatibility run.

## The substrate certification procedure incorporates several processes.

An initial screening evaluation is followed by a more comprehensive evaluation

#### looking at the performance of the particular substrate within the press. This checks for:

### **Runnability:**

The ability of the substrate to run smoothly through the press in various print modes.

### Fixing:

Ink-substrate interaction as determined by: 1) The degree of ink adhesion to the substrate for standard and photo-related applications as measured in a tape peel test of the image; and 2) The degree of flaking of the ink layer. The fixing properties are measured through a range of blanket temperatures and pressures.

### **Blanket Compatibility:**

Blanket-substrate interaction as determined by: 1) Ink-transferability, which is the quality of ink transfer from the blanket to the substrate as reflected in highlight dots, thin lines, heavy images and image edge integrity; 2) 'Blanket Memory' effects, reflected in gloss or density differences between solids and background areas of the previously printed image; and 3) Number of cleaner pages, in which blankets are routinely maintained by performing a self cleaning procedure ("cleaner pages") used to refresh the blanket's release layer.

#### **Photo and White Ink Applications:**

Use of robust media products is strongly recommended when printing photo-related and/or white ink applications and/or Light Cyan and Light Magenta due to additional ink coverage demands of these applications. This media has been tested and approved to perform well with higher levels of ink coverage, and is therefore recommended for photo-related and/or white ink type applications. However, it is strongly recommended that user acceptance ultimately be evaluated per individual application and finishing requirements, etc. The test results are provided as a guide; assess actual performance to determine suitability for individual use.

#### **Star Rating**

★★★ Best performing substrate: fewer print cleaners needed; no blanket memories at least up to 12K impressions.

- ★★ Recommended substrate: some print cleaners may be needed; slight memories may be seen up to 12K impression
  - 🚖 Good substrate: print cleaners generally required; some memories may be seen by 12K impressions.

|                |  | ***   | **   | *  |   |
|----------------|--|---|--|--|---|
| Evaluation     | Measurement  | Best-performing Recommended                           |  | Good   | Failure   |
| Transport      | Runnability  | No jams with the tested paper                         | No more than 1 jam or minor<br>issue with the tested paper | No more than 1 jam and minor<br>issues with the tested paper | 2 jams with the tested paper, control performs well |
| Fixing         | Peeling  | All 4 results are $\ge$ 90%                           | All 4 results are $\ge 80\%$                               | At least 1 result is ≥ 80%                                   | All results < 80%                                   |
| Flaking Guille | otine, 5min • Coated                                   | All results are > 250%                                | At least 1 result is > 250%                                | At least 1 result is > 200%                                  | Results < 200%                                      |
| Flaking Guilla | Flaking Guillotine, 5min • Uncoated                    |   | Result is > 250%   | Result is > 200%   | Results < 200%                                      |
| Photo          | Peeling 290% Black                                     | Result is > 80% after 10 or 60 minutes                |  | N/A  | Results < 80%                                       |
| FIIOIO         | Flaking Guillotine, 5min                               | <1mm  | at 350% K  | N/A  | Results > 1mm                                       |
| Blanket        | Cleaner Sheets   | 1ª Red is clean 3ª Red is clean                       |  | 5 <sup>th</sup> Red is clean                                 | 5th Red not clean,<br>or White observed             |
| Compatibility  | Monitors on tested paper<br>and reference glossy paper | Very minor memories at least<br>up to 12K impressions |  |  | Severe lack of dots/cracks/gloss<br>memory          |

This substrate is certified for the next two years from the date of evaluation, provided there is no change to the paper properties or production processes. At the end of two years from the original evaluation date, if there have been no changes in paper properties or production processes, the certification can be extended for another two years. After four years from the original certification date, a new certification is required.



